

VEHICLE SYSTEM

Background Information

The present invention is directed to a vehicle system for operation in a motor vehicle according to the definition of the species in the independent claim.

5 Vehicle systems are known in the form of vehicle navigation systems which output driving directions for guiding a vehicle driver along a previously computed route to a destination in acoustic and/or visual form. To compute the travel route, the driver must previously input the destination via an operator
10 interface of the vehicle navigation system. Since inputting the destination while driving causes considerable distraction from the traffic situation, it has been discussed to suppress the operation of the device, in particular destination input, while the vehicle is in motion (referred to hereinafter as the
15 "speed lock function").

DE 199 52 857 C1 describes a device for controlling vehicle components as a function of the driver's condition, in which the driver's condition is determined and the information to be displayed is filtered as a function thereof. Operation and
20 control by the driver is thus improved and safety is enhanced because the driver is less distracted. This device limits the operation of a functionality of the electronic device as a function of the situation. For example, the destination input of a navigation device may not be used or a TV set may not be
25 turned on during travel. Full use or partial functionality of an application of the electronic device may also be turned on or off as a function of the speed of travel.

Older German patent application 102 55 435.8 (not a prior publication) describes a driver information system having an

operator control in which operation at a certain detected speed of the vehicle is at least limited, i.e., having the above-described speed lock function; however, this limitation may be at least partially cancelled if, for example, occupancy
5 of the front-seat passenger seat has been determined by a seat belt fastener sensor or a weight sensor. This approach assumes that, in the case of an occupied front-seat passenger seat, the front-seat passenger actually operates the driver information system; however, operation by the vehicle driver
10 is not ruled out. In practice, it has been found that, even if the front-seat passenger seat is occupied, the vehicle driver often assumes operation of the device.

Advantages of the Invention

15 The vehicle system according to the present invention having the features of the independent patent claim has the advantage over the related art that operation of the system is influenced depending on whether the vehicle driver or another occupant of the vehicle is accessing the vehicle system.
20 Operating access which may excessively distract the vehicle driver from the actual driving task is thus effectively disabled. At the same time, the vehicle system remains fully, or at least largely, operational for other vehicle occupants. Operation is understood in the context of the present
25 invention primarily as inputs by the operator into the vehicle system, but also as outputs of the vehicle system to the user.

In the case of a navigation system, for example, the front-seat passenger may thus assume operation of the navigation system while the vehicle is in motion in particular. Operation
30 during travel may be necessary, for example, if the travel route is modified manually due to traffic problems not taken into account when the route was computed or to errors in the navigation data material.

When traveling with a front-seat passenger, additional inputs are thus possible and unnecessary stops are avoided, which contributes to safety. The present invention provides for limitation of operation which goes beyond that of the conventional speed lock function in the case of operating access by the vehicle driver, in particular within the speed lock function, i.e., while the vehicle is in motion.

In each case, the present invention increases user acceptance of the speed lock function and ensures a competitive advantage.

Drawing

Exemplary embodiments of the present invention are illustrated in the drawing and explained in greater detail below.

Figure 1 shows a block diagram of the portion essential to the present invention of the vehicle system according to the present invention;

Figure 2 shows a flow chart of the essential portion of a software program running in a controller of the vehicle system.

Detailed Description of the Exemplary Embodiments

The vehicle system according to the present invention is described in detail below using the example of a vehicle navigation system. This, however, does not mean that the present invention is limited to vehicle navigation systems.

Rather, the present invention is also applicable to other vehicle systems such as car radios or a cell phone operated in a vehicle.

Vehicle system 1 according to the present invention includes an input device 13 having control elements not depicted in detail in the figure, preferably momentary-contact switches and/or incremental rotary transducers, for inputting commands and/or operating parameters into vehicle system 1. In the case

of a vehicle navigation system, the above-described control elements, combined for example with a controller 12 of the navigation system, are used for inputting a destination for a subsequent route computation from the current location to the destination and subsequent navigation. In the case of a cell phone, the control elements are used, for example, for dialing a certain telephone number of a desired conversation partner or for answering an incoming telephone call.

Vehicle navigation system 1 according to the present invention also includes an output device 14, which is preferably designed as a visual and/or acoustic output. In the case of a vehicle navigation system, output device 14, combined with the navigation device, is used for outputting driving directions to guide the vehicle driver in the form of spoken driving directions and/or directional arrows displayed on a display device. Alternatively or additionally, a map display may be provided, on which the computed route or a portion thereof is displayed to orient the driver.

Furthermore, output device 14 combined with the destination input is used, for example, for displaying selectable destinations and/or a map display, on which a destination may be marked with the aid of a cursor operable via the control elements of input device 13.

In the case of a car radio, output device 14 includes, for example, the display of the car radio which, in addition to the name or the receiving frequency of a currently set broadcast station, displays variable information transmitted using the radio data system (RDS) such as title and performer of a song currently being transmitted or running text such as advertising, for example.

Input device 13 and output device 14, both connected to controller 12, together form an operator control 15 of the vehicle system according to the present invention.

Means 11, designed for detecting whether the driver or another vehicle occupant is accessing operator control 15 of vehicle system 11, is also connected to controller 12 of the vehicle system according to the present invention and generates an appropriate access detection signal as a function of the person accessing the system.

For this purpose, access detection means 11 includes sensors for detecting information on the basis of which it is possible to determine which of the vehicle occupants is accessing operator control 15 for operating vehicle system 1.

In a first embodiment of the operator detection means, this sensor system includes a camera 115, whose imaging range includes at least driver seat (2) or the front-seat passenger seat (3), but preferably both the driver and the front-seat passenger seats. The image information recorded by the camera is processed in a first software module 111 of controller 12 and a signal is derived therefrom, which indicates whether driver 2 or front-seat passenger 3 is accessing operator control 15, in particular the control elements of input device 13.

The exact mode of operation of first software module 111 for deriving one of the vehicle occupants accessing the system is not the object of the present invention and will therefore not be described in more detail. The principle involved is abundantly known from the literature. Reference is made to the overview article, D. M. Gavrila: "The Visual Analysis of Human Movement: A Survey" in Computer Vision and Image Understanding, vol. 73, no. 1, January, pp. 82-98, 1999, in which approaches to this problem are described and to whose entire disclosure content regarding driver or front-seat passenger detection reference is hereby made.

An image pattern comparison, for example, is suitable for this purpose, an image previously recorded and stored as part of

the software component, for example, of the hand or also the arm and possibly the upper body of the front-seat passenger accessing the system being used as a basis for the comparison. Alternatively, three-dimensional or other image detection algorithms may also be used.

In the context of the present invention, it is only essential that first software component 111 is capable of using the image signals of camera 115 to unambiguously determine whether the hand of driver 2 or hand 31 of front-seat passenger 3 is accessing the control elements of input device 13 of vehicle system 1.

According to an advantageous variant of this first embodiment of access detection means 11, instead of a single camera 115 at least two video sensors are provided at a distance from one another or a multicamera video sensor is provided. The stereo or multichannel image information detected by this sensor system allows three-dimensional detection of the driver or front-seat passenger seat, or the driver or front-seat passenger.

According to a refinement of the first embodiment, the gray scale value information contained in the video signals is also analyzed for the purpose of access detection 11.

According to another advantageous version of this first embodiment, access determination means (11) operates by the principle of depth sensors, which in the present case of a video sensor system are based on the principle of structured lighting.

Both the evaluation of stereo or multichannel video information and the principle of structured lighting are described in detail in the related art and, for example, in X. Jiang "Dreidimensionales Computersehen" [Three-dimensional computer viewing], Springer-Verlag, Berlin Heidelberg, to

which express reference is hereby made, so that a detailed explanation of these principles may be omitted here.

A second embodiment of operator detection device 11 is based on the assumption that vehicle system 1 is at least partly, in particular with respect to its more complex operating functions, operated via spoken commands. At least one microphone 112 is required to detect the spoken commands. The microphone is situated within a hands-free device for a cell phone, preferably in front of the driver seat in or on the vehicle dashboard. At least one second microphone 113 which is installed spatially separated from first microphone 112, preferably in front of the front-seat passenger seat in the dashboard of the motor vehicle is provided for detecting whether the verbal commands have been given by vehicle driver 2 or front-seat passenger 3. The signals of both the first and second microphone are supplied to first software component 111 of controller 12, which uses the difference in propagation time between the signals of the first and second microphone, for example, via cross-correlation of the two microphone signals, to determine whether driver 2 or front-seat passenger 3 has issued the verbal commands. This is made possible by the above-described location of microphones 112 and 113, because, for example, the commands issued by vehicle driver 2 to second microphone 113 need a longer propagation time than those issued to first microphone 112 situated in front of the driver. The same is true for the commands issued by front-seat passenger 3.

Additional embodiments of access detection means 11 is directed in particular to an alternative sensor system.

The access detection means may thus also include a radar sensor system instead of the above-described sensor system.

Access detection means 11 may also include a sensor system which operates and evaluates signals on the basis of a depth

sensor by the propagation time principle or the laser scanner principle.

These alternative measuring and evaluation methods are also abundantly known from the related art, for example, from R.

5 Schwarte et al. "New Powerful Sensory Tool in Automotive Safety Systems Based on PMD-Technology," Advanced Microsystems for Automotive Applications 2000, Springer-Verlag, Berlin Heidelberg, 2000, to which publication reference is hereby expressly made, so that a detailed explanation of these
10 principles may be omitted here.

According to a first, simple embodiment of the operation control, the operation, i.e., operability of vehicle system 1 is controlled on the basis of the detected operator, in particular driver 2 or other occupant 3 of the vehicle. For
15 this purpose, controller 12 includes a second software component, which further processes the signal of operator detection means 11 and controls operator control 15, in particular the scope of its functions, on the basis thereof. The control of the operation of vehicle system 1 includes in
20 particular limiting or enabling of operation functionalities as a function of the vehicle occupant operating the system. The vehicle driver may thus only have access to a limited operator interface, i.e., a limited scope of functions 13 and a limited selection of functions of operator guidance 14,
25 while front-seat passenger 3 may access the entire range of operations of vehicle system 1.

According to a preferred embodiment of the present invention, additional means 16 is provided in controller 12 of vehicle system 1 according to the present invention for generating at
30 least one signal indicating the motion status, in particular motion as opposed to a standstill, of the motor vehicle. This may be a tachometer signal generator 162, which generates a signal indicating the instantaneous vehicle velocity. In the case of a vehicle navigation system 1, means 16 may also include a GPS

receiver, which analyzes position data about the instantaneous vehicle position and derives a signal indicating the instantaneous motion status of the vehicle therefrom.

5 The signals indicating the motion status of the vehicle, for example, the signals of tacho signal generator 162 are supplied to an analyzer 163, which is preferably designed as a component of the controller in the form of a third software routine. Analyzer 162 is designed to use the signals indicating the motion status of the vehicle to determine
10 whether the vehicle is at a standstill, is moving, or is moving at a certain minimum velocity.

Signal generator 162 and analyzer 161 form a device 16 for detecting motion of the vehicle.

15 According to the preferred second embodiment of the operating control, which is based on the preferred embodiment of the vehicle system having motion detection device 16, the operation of vehicle system 1 is controlled as a function of both the vehicle's motion status and detected operator 2 or 3 of vehicle system 1.

20 This is explained below using the example of a vehicle navigation system in a motor vehicle, taking into account the flow chart of Figure 2.

A distinction is made between three states.

1. Vehicle at a standstill

25 On the basis of the motion data acquired by sensor system 162, motion detection means 16 detects that the vehicle is at a standstill (step 21 - alternative "no"). For this case, controller 12 enables operation of the full range of vehicle navigation system 1 (step 23). This means that, for example, a
30 destination, i.e., the name of the destination in particular and a corresponding street name, may be input via control elements of input device 13 of the navigation system,

inputting being supported by navigation system 1 via appropriate displays, for example, of proposed names, on display device 14, on the basis of input letters.

2. Vehicle in motion, operating access by driver 2

5 Motion detection means 16 uses the motion data detected by sensor system 162 to determine that the vehicle is in motion (step 21, alternative "yes"). Furthermore, the access detection means detects that the vehicle driver is accessing operator control 15 (step 22, alternative "yes"), i.e., the
10 hand of driver 2 is in the area of input device 2 of vehicle navigation system 1, and a control element of vehicle navigation system 1 is being actuated. Alternatively, this access status may also be identified by the fact that a control element of input device 13 is operated and hand 31 of
15 the front-seat passenger is not in the area of input device 13 of the vehicle navigation system.

In this case, controller 12 controls the functions of navigation system 1 in such a way that it restricts or simplifies the outputs directed at the vehicle driver by
20 output device 14 to maximally reduce the distraction of vehicle driver 2 from the traffic situation. In the present example of the vehicle navigation system, for example, a map display having a route drawn in is replaced while the vehicle is in motion by the display of simple and easy-to-grasp turn
25 arrows and by a simple verbal turn direction. Thus, in particular, complex directions such as "please turn left onto Hilderheimer Strasse in 500 m, please reduce speed, sharp curve" are replaced by shorter and easier-to-grasp directions such as "left now" or "next street on the left."

30 Furthermore, controller 12 completely locks input device 13 of operator control 15 for inputs by driver 2, i.e., it implements the essentially known speed lock function as defined above (step 25).

3. Vehicle in motion, operating access by front-seat passenger 3

Motion detection means 16 detects motion of the vehicle on the basis of the motion data detected by sensor system 162 (step 5 21, alternative "yes"). Furthermore, access detection means 11 determines that front-seat passenger 3 is accessing operator control 15 (step 22, alternative "no"), i.e., hand 31 of front-seat passenger 3 is in the area of input device 13 of vehicle navigation system 1, and a control element of vehicle 10 navigation system 1 is being actuated. Alternatively, this access status may also be identified by the fact that a control element of input device 13 is being actuated and the hand of driver 2 is not in the area of input device 13 of vehicle navigation system 1.

15 For this case, controller 12 allows at least a limited or, depending on the embodiment of the present invention, even full operability of vehicle system 1 (step 24). In this case, i.e., with the vehicle in motion and operating access by front-seat passenger 3, controller 12 preferably enables all 20 display possibilities and input procedures which are also enabled with the vehicle at a standstill, because these may be performed by front-seat passenger 3, who does not have to concentrate on driving the vehicle. However, the outputs intended primarily directly for the vehicle driver engaged in 25 the task of driving are preferably output in a simple and therefore easy-to-grasp form as described previously.

Alternatively (step 24), the acoustic driving directions of navigation system 1 may also be output in an easy-to-grasp, abbreviated form here, whereas a detailed map with the route 30 of travel drawn in appears on the display of the vehicle navigation system, so that it is able to be understood by the front-seat passenger, who then may impart explanatory or additional directions to the vehicle driver. Furthermore, this

alternative allows the front-seat passenger to better understand and, if necessary, to correct the route.

Furthermore, the range of operability for operating access by front-seat passenger 3 with the vehicle in motion may be

5 individually settable.

When separate output and/or input devices are available to the driver and the front-seat passenger, as is the case of individual entertainment systems for the backseat passengers, or when an additional display device is available, for

10 example, in a combo instrument in addition to the display of the vehicle system provided in the center console, additional operating strategies may be advantageously provided. Thus, in the case of a vehicle in motion and operating access by front-seat passenger 3, simple directional arrows may be displayed,
15 for example, to driver 2 by the additional display in the combo instrument for navigation, while a detailed map with the route drawn in is made available to the front-seat passenger on the display in the center console display or front seat head support. Furthermore, operation by front-seat passenger 3
20 may be enabled by allowing the front-seat passenger to set any desired map detail or zoom factor via the input device, while only the directional arrows continue to be displayed to driver 2.

Controller 12 thus achieves motion-dependent and operator-dependent control of the operation of vehicle system 1 by
25 operator control 15.